


## DOMETIC COOLMATIC CRP 40 / CRP 40S

Compressor refrigerators, 12 / 24 V DC



	CRP 40	CRP 40S
<b>Storage volume</b> freezer compartment	39 l 5.3 l	
<b>Connections</b>	12 / 24 V DC	
<b>Average power consumption</b>	45 W	
<b>Current consumption at 12 V</b>	1.5 Ah/h at +25 °C ambient temperature, 1.8 Ah/h at +32 °C ambient temperature, both at +5 °C interior temperature	
<b>Refrigerant</b>	R134a, Refrigerant quantity: 38 g, CO <sub>2</sub> equivalent: 0.054 t, Global warming potential (GWP): 1430	
<b>Insulation</b>	PU foam all around	
<b>System</b>	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, mechanical, continuously variable thermostat	
<b>Material</b>	Body: with coated metal frame Plastic interior/door frame: plastic, Fittings: stainless steel	Body: with coated metal frame Interior: plastic, fittings: stainless steel Door: stainless steel (AISI316)
<b>Colour</b>	Cabinet: black Door frame: silver Door panel: matt-silver (brushed stainless steel appearance)	Cabinet: black Door frame: silver Door panel: stainless steel (V4A)
<b>Quality features</b>	Matt-silver decorative panel, brackets secure bottles	High-quality stainless steel front, brackets secure bottles
<b>Weight</b>	19 kg	21 kg
<b>Test marks</b>	TÜV/GS, e-certified (Automotive EMC Directive)	
<b>Product</b>	<b>Ref. No.</b>	
Dometic CoolMatic CRP 40	9105204517	
Dometic CoolMatic CRP 40S	9105204441	
<b>/ Optional extras</b>		
Mains adapter MPS 35, 110–240 V > 24 V	9600000445	
Standard installation frame CRP 40	9105306405	
Standard installation frame CRP 40S	9105305676	
Flush-mount installation frame CRP 40	9105306410	
Flush-mount installation frame CRP 40S	9105305671	