





DOMETIC COOLMATIC CRX 50 / 50S / 65 / 65S

Compressor refrigerators, 12 / 24 V DC

		CRX 50	CRX 50S	
<p>CRX 50/50S</p>  	Storage volume freezer compartment	45 l 4.4 l		
	Connections	12 / 24 V DC		
	Average power consumption	40 W		
	Current consumption at 12 V	1.1 Ah/h at +25 °C ambient temperature, 1.7 Ah/h at +32 °C ambient temperature, both at +5 °C interior temperature		
	Refrigerant	R134a, Refrigerant quantity: 38 g, CO ₂ equivalent: 0.054 t, Global warming potential (GWP): 1430		
	Insulation	PU foam all around		
	System	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, mechanical, continuously variable thermostat		
	Material	Body: with coated metal frame Plastic interior/door frame: plastic, Fittings: stainless steel	Body: with coated metal frame Interior: plastic, fittings: stainless steel Door: stainless steel (AISI316)	
	Colour	Cabinet: black Door frame: silver Door panel: matt-silver (brushed stainless steel appearance)	Cabinet: black Door frame: silver Door panel: stainless steel (V4A)	
	Quality features	Matt-silver decorative panel, brackets secure bottles	High-quality stainless steel front, brackets secure bottles	
Weight	17 kg			
Test marks	TÜV/GS, e-certified (Automotive EMC Directive)			
		CRX 65	CRX 65S	
<p>CRX 65/65S</p>  	Storage volume freezer compartment	57 l 7 l		
	Average power consumption	45 W		
	Refrigerant	R134a, Refrigerant quantity: 42 g, CO ₂ equivalent: 0.060 t, Global warming potential (GWP): 1430		
	Current consumption at 12 V	1.14 Ah/h at +25 °C ambient temperature, 1.8 Ah/h at +32 °C ambient temperature, both at +5 °C interior temperature		
	Weight	18 kg	19 kg	
	Further technical data as for CRX 50/CRX 50S			
	Product		Ref. No.	
	Dometic CoolMatic CRX 50		9105306565	
	Dometic CoolMatic CRX 50S		9105306566	
	Dometic CoolMatic CRX 65		9105306568	
Dometic CoolMatic CRX 65S		9105306569		
/ Optional extras				
Mains adapter MPS 35, 110–240 V > 24 V		9600000445		
Standard installation frame CRX 50		9105306405		
Standard installation frame CRX 50S		9105305676		
Flush-mount installation frame CRX 50		9105306410		
Flush-mount installation frame CRX 50S		9105305671		
Standard installation frame CRX 65		9105306406		
Standard installation frame CRX 65S		9105305677		
Flush-mount installation frame CRX 65		9105306411		
Flush-mount installation frame CRX 65S		9105305672		