


## DOMETIC COOLMATIC CRX 80 / 80S / 110 / 110S

Compressor refrigerators, 12 / 24 V DC

		CRX 80	CRX 80S	
<p>CRX 80/80S</p>  	<b>Storage volume</b> freezer compartment	78 l 7.5 l		
	<b>Connections</b>	12 / 24 V DC		
	<b>Average power consumption</b>	48 W		
	<b>Current consumption at 12 V</b>	1.19 Ah/h at +25 °C ambient temperature, 2.0 Ah/h at +32 °C ambient temperature, both at +5 °C interior temperature		
	<b>Refrigerant</b>	R134a, Refrigerant quantity: 48 g, CO <sub>2</sub> equivalent: 0.069 t, Global warming potential (GWP): 1430		
	<b>Insulation</b>	PU foam all around		
	<b>System</b>	Fully hermetic compressor with integrated control electronics, low-voltage protection / electronic fuse, automatic reverse pole protection, mechanical, continuously variable thermostat		
	<b>Material</b>	Body: with coated metal frame Plastic interior/door frame: plastic, Fittings: stainless steel	Body: with coated metal frame Interior: plastic, fittings: stainless steel Door: stainless steel (AISI316)	
	<b>Colour</b>	Cabinet: black Door frame: silver Door panel: matt-silver (brushed stainless steel appearance)	Cabinet: black Door frame: silver Door panel: stainless steel (V4A)	
	<b>Quality features</b>	Matt-silver decorative panel, brackets secure bottles	High-quality stainless steel front, brackets secure bottles	
<b>Weight</b>	20 kg	21 kg		
<b>Test marks</b>	TÜV/GS, e-certified (Automotive EMC Directive)			
		CRX 110	CRX 110S	
<p>CRX 110 / 110S</p>  	<b>Storage volume</b> freezer compartment	104 l 9 l		
	<b>Average power consumption</b>	50 W		
	<b>Current consumption at 12 V</b>	1.8 Ah/h at +25 °C ambient temperature, 2.4 Ah/h at +32 °C ambient temperature, both at +5 °C interior temperature		
	<b>Refrigerant</b>	R134a, Refrigerant quantity: 47 g, CO <sub>2</sub> equivalent: 0.067 t, Global warming potential (GWP): 1430		
	<b>Weight</b>	22.5 kg	23.5 kg	
	<b>Further technical data as for CRX 80/CRX 80S</b>			
	<b>Product</b>		<b>Ref. No.</b>	
	Dometic CoolMatic CRX 80		9105306570	
	Dometic CoolMatic CRX 80S		9105306571	
	Dometic CoolMatic CRX 110		9105306572	
Dometic CoolMatic CRX 110S		9105306573		
<b>/ Optional extras</b>				
Mains adapter MPS 35, 110–240 V > 24 V		9600000445		
Standard installation frame CRX 80		9105306407		
Standard installation frame CRX 80S		9105305678		
Flush-mount installation frame CRX 80		9105306412		
Flush-mount installation frame CRX 80S		9105305673		
Standard installation frame CRX 110		9105306408		
Standard installation frame CRX 110S		9105305679		
Flush-mount installation frame CRX 110		9105306413		
Flush-mount installation frame CRX 110S		9105305674		